

**IN THE CLAIMS**

**Clean version of original claims 1-20 and subsequently added claims 21-60**

Please amend claim 16 to read as follows:

1           1. (Amended) A negative pressure air bearing slider, comprising:  
2           a slider body for flying above a surface of a recording disc during relative rotation of the  
3           disc, the slider body having a principal surface for confronting the surface of the disc, said  
4           principal surface having a lead portion, a rear portion, a first side portion and a second side  
5           portion, wherein the lead portion is spaced upstream of the rear portion relative to a longitudinal  
6           direction of said slider body which is coincident with a tangential rotational direction of the  
7           recording disc, and wherein the first side portion is spaced from the second side portion relative  
8           to a lateral direction of said slider body;  
9           first and second projections extending from said lead portion of said principal surface of  
10          said slider body to define first and second air bearing surfaces, said first and second air bearing  
11          surfaces [spaced apart from each other] extending in the lateral direction of said slider body[;]  
12          and forming  
13          a U-shaped projection extending from said principal surface of said slider body, said U-  
14          shaped projection including an arcuate front wall portion [at least partially located between said  
15          first and second air bearing surfaces], said U-shaped projection further including first and second  
16          side wall portions extending from opposite ends of said arcuate front wall rearwardly toward said

17 rear portion and outwardly toward said first and second side portions of said principal surface for  
18 defining a negative pressure cavity therein, said first and second wall portions terminating at said  
19 rear portion of said [principle] principal surface of said slider body for defining third and fourth  
20 air bearing surfaces, said third and fourth air bearing surfaces spaced apart from each other along  
21 said lateral direction of said slider body [and spaced apart from said first and second air bearing  
22 surfaces along said longitudinal direction of said slider body; a fourth projection extending from  
23 said rear portion of said principal surface of said slider body, said fourth projection interposed  
24 between said third and fourth air bearing surfaces and generally aligned with said longitudinal  
25 direction of said slider body; and

26 a transducer mounted on a rear edge of said fourth projection for establishing pseudo  
27 contact with the disc surface while said slider body is flying above said disc surface].

1 2. The negative pressure air bearing slider as claimed in claim 1, wherein said U-shaped  
2 projection is axisymmetrical about a longitudinal axis of said slider body.

1 3. The negative pressure air bearing slider as claimed in claim 2, wherein said first and  
2 said second air bearing surfaces are symmetric about said longitudinal axis of said slider body.

1 4. The negative pressure air bearing slider as claimed in claim 2, wherein said first and  
2 said second air bearing surfaces are respectively longitudinally aligned with said third and fourth  
3 air bearing surfaces, and wherein said negative pressure cavity is centrally located between said

4 air bearing surfaces.

1 5. The negative pressure air bearing slider as claimed in claim 1, wherein each of said  
2 first and said second air bearing surfaces include a tapered surface portion, the tapered surface  
3 portion tapering from each air bearing surface toward a lead edge of said slider body.

1 6. The negative pressure air bearing slider as claimed in claim 1, wherein each of said  
2 first and said second air bearing surfaces include a stepped down surface portion, the stepped  
3 down surface portion extending from each air bearing surface to a lead edge of said slider body.

1 7. The negative pressure air bearing slider as claimed in claim 1, wherein an interface  
2 region between said arcuate front wall portion and said first side wall portion includes a first  
3 stepped down surface portion extending between said third air bearing surface and an inner edge  
4 of said slider body, and wherein an interface region between said arcuate front wall portion and  
5 said second side wall portion includes a second stepped down surface portion extending between  
6 said fourth air bearing surface and an outer edge of said slider body.

1 8. The negative pressure air bearing slider as claimed in claim 1, wherein an interface  
2 region between said arcuate front wall portion and said first side wall portion includes a first  
3 stepped down surface portion extending between said third air bearing surface and said negative  
4 pressure cavity, and wherein an interface region between said arcuate front wall portion and said

5 second side wall portion includes a second stepped down surface portion extending between said  
6 fourth air bearing surface and said negative pressure cavity.

1 9. The negative pressure air bearing slider as claimed in claim 8, wherein the interface  
2 region between said arcuate front wall portion and said first side wall portion further includes a  
3 third stepped down surface portion extending between said third air bearing surface and said  
4 negative pressure cavity, and wherein the interface region between said arcuate front wall portion  
5 and said second side wall portion further includes a fourth stepped down surface portion  
6 extending between said fourth air bearing surface and said negative pressure cavity.

1 10. The negative pressure air bearing slider as claimed in claim 1, wherein an elongated  
2 groove is provided in said arcuate front wall portion, said groove extending between said first  
3 and second side wall portions.

1 11. (Amended) The negative pressure air bearing slider as claimed in claim 1, wherein  
2 an opening is provided in said arcuate front wall portion, said opening located between said first  
3 and second side wall portions and extending to said [principle] principal surface of said slider  
4 body.

1 12. The negative pressure air bearing slider as claimed in claim 11, wherein said opening  
2 is offset from a longitudinal axis of said slider body.

1           13. The negative pressure air bearing slider as claimed in claim 11, wherein said opening  
2 is symmetrical about a longitudinal axis of said slider body.

1           14. The negative pressure air bearing slider as claimed in claim 10, wherein said  
2 elongated groove in said arcuate front wall portion is symmetrical about a longitudinal axis of  
3 said slider body.

1           15. The negative pressure air bearing slider as claimed in claim 10, wherein said  
2 elongated groove in said arcuate front wall portion is offset about a longitudinal axis of said  
3 slider body.

1           16. (Twice Amended) A negative pressure air bearing slider, comprising:  
2           a slider body for flying above a surface of a recording disc during relative rotation of the  
3 disc, the slider body having a principal surface facing the surface of the disc, said slider body  
4 having a lead edge, a rear edge, a first side edge and a second side edge, wherein the lead edge is  
5 spaced upstream of the rear edge along a longitudinal axis of said slider body, the longitudinal  
6 axis coincident with a tangential rotational direction of the recording disc, and wherein the first  
7 side edge is spaced from the second side edge along a latitudinal axis of said slider body;  
8           first and second projections extending from a lead portion of said principal surface  
9 [adjacent to said lead edge] to provide first and second air bearing surfaces, said first and second

10 air bearing surfaces spaced apart from each other along said latitudinal axis and located proximal  
11 to said first and second side edges of said slider body [such that a gap is provided there between;]  
12 and forming a U-shaped projection extending from said principal surface of said slider body, said  
13 U-shaped projection including an arcuate front wall and first and second side walls extending  
14 from each end of said front wall, each of said side walls extending rearwardly toward said rear  
15 portion and outwardly toward an adjacent side edge of said slider body for defining a negative  
16 pressure cavity therein, a forwardmost portion of said arcuate front wall located at least partially  
17 between said first and second air bearing surfaces such that first and second passages are formed  
18 between the arcuate front wall and a rear edge of said first and second air bearing surfaces, said  
19 passages communicating with said gap to provide a flow path that extends from said lead portion  
20 and terminates along said side edges prior to reaching a rear portion of said slider body adjacent  
21 to said rear edge thereof, said first and second wall portions terminating at said rear portion of  
22 said slider body for defining third and fourth air bearing surfaces spaced apart along said  
23 latitudinal axis and located proximal to said first and second side edges of said slider body, the  
24 air bearing surfaces positioned about on said [principle] principal surface of said slider body such  
25 that four separate and distinct positive pressure areas are provided when said slider body is flying  
26 above said rotating disc; and

27 a fourth projection extending from said rear portion of said slider body, said fourth  
28 projection generally aligned with said longitudinal axis of said slider body, the fourth projection  
29 including a transducer mounted on a rear edge thereof for establishing pseudo contact with the  
30 disc surface while said slider body is flying above said disc.

1           17. The negative pressure air bearing slider of claim 16 wherein said forward most  
2           portion of said arcuate front wall is aligned generally with said longitudinal axis of said slider  
3           body.

1           18. The negative pressure air bearing slider of claim 16 wherein said negative pressure  
2           cavity is generally rounded.

1           19. The negative pressure air bearing slider of claim 16 wherein each of the passages of  
2           said flow path extend tangentially to said longitudinal axis of said slider body.

1           20. The negative pressure air bearing slider of claim 16 wherein each of the passages and  
2           said gap of said flow path coact to provide a wide flow path.

1           21. (Amended) A negative pressure air bearing slider having a negative pressure cavity,  
2           comprising:

3           a body with a principal surface disposed to confront a recording surface of a recording  
4           medium, said principal surface having a lead portion and a rear portion, said lead portion being  
5           spaced upstream from said rear portion relative to a rotational direction of any recording medium  
6           confronted by said slider, said lead portion having a front edge, said rear portion having a rear  
7           edge, said front edge and said rear edge together defining boundaries of said principal surface in

8 a longitudinal direction of said slider body; and

9 a U-shaped air bearing platform defining a negative pressure cavity on said principal  
10 surface, said U-shaped air bearing platform comprising not more than two separate air bearing  
11 platforms each extending rearwardly toward said rear portion of said principal surface and  
12 respectively terminating at a first rear termination and a second rear termination, at least one of  
13 said not more than two separate air bearing platforms including a side wall portion;

14 at least one of said first rear termination and said second rear termination not coinciding  
15 with said rear edge, and being disposed upstream of said rear edge relative to said rotational  
16 direction of said recording medium.

1 22. The negative pressure air bearing slider according to claim 21, further comprising:  
2 a gap disposed within said cross rail portion.

1 23. The negative pressure air bearing slider according to claim 22, wherein:  
2 said gap is centered with respect to a longitudinal axis of said slider body.

1 24. The negative pressure air bearing slider according to claim 22, wherein:  
2 said gap is off-centered with respect to a longitudinal axis of said slider body.

1 25. The negative pressure air bearing slider according to claim 21, further comprising:  
2 a recessed step disposed within said cross rail portion.



1        26. The negative pressure air bearing slider according to claim 25, wherein:  
2        said recessed step is centered with respect to a longitudinal axis of said slider body.

1        27. The negative pressure air bearing slider according to claim 25, wherein:  
2        said recessed step is off-centered with respect to a longitudinal axis of said slider body.

1        28. The negative pressure air bearing slider according to claim 21, further comprising:  
2        a first front air bearing platform; and  
3        a second front air bearing platform;  
4        said first and said second front air bearing platforms being disposed on opposite sides of  
5        said principal surface symmetrically about a longitudinal axis of said slider body, said first and  
6        second front air bearing platforms being disposed upstream of said U-shaped air bearing platform  
7        relative to a rotational direction of said recording medium.

1        29. The negative pressure air bearing slider according to claim 28, wherein:  
2        a tapered surface portion is interposed between said front edge and each of said first and  
3        said second front air bearing platforms, the tapered surface portion tapering from each air bearing  
4        surface toward said front edge of said slider body.

1        30. The negative pressure air bearing slider according to claim 21, further comprising:

2        a rear air bearing platform accommodating mounting of a transducer, said rear air bearing  
3        platform being spaced downstream of said U-shaped air bearing platform relative to a rotational  
4        direction of said recording medium, and being centered with respect to a longitudinal axis of said  
5        slider body.

1        31. (Amended) A negative pressure air bearing slider, comprising:  
2        a principal surface defining a first plane tangential to a first direction;  
3        said principal surface having a lead portion and a rear portion, said lead portion being  
4        spaced upstream from said rear portion relative to said first direction, said lead portion having a  
5        front edge, said rear portion having a rear edge, said front edge and said rear edge together  
6        defining longitudinal boundaries of said principal surface in said first direction; and  
7        a U-shaped air bearing platform having a plurality of air bearing surfaces surrounding a  
8        negative pressure cavity while defining a second plane tangential to said first direction, said U-  
9        shaped air bearing platform comprising not more than two separate air bearing platforms each  
10       extending from said lead portion rearwardly toward said rear portion and respectively terminating  
11       at a first rear termination and a second rear termination, at least one of said not more than two  
12       separate air bearing platforms including a side wall portion;  
13       at least one of a surface between said first rear termination and said rear edge and a  
14       surface between said second rear termination and said rear edge being in said first plane.

1        32. The negative pressure air bearing slider according to claim 31, wherein said U-

2 shaped air bearing platform further comprising:

3 a cross rail portion extending generally laterally across said principal surface.

1 33. The negative pressure air bearing slider according to claim 32, further comprising:

2 a gap disposed within said cross rail portion.

1 34. The negative pressure air bearing slider according to claim 33, wherein:

2 said gap is centered with respect to a longitudinal axis of said slider body.

1 35. The negative pressure air bearing slider according to claim 33, wherein:

2 said gap is off-centered with respect to a longitudinal axis of said slider body.

1 36. The negative pressure air bearing slider according to claim 32, further comprising:

2 a recessed step disposed within said cross rail portion.

1 37. The negative pressure air bearing slider according to claim 36, wherein:

2 said recessed step is centered with respect to a longitudinal axis of said slider body.

1 38. The negative pressure air bearing slider according to claim 36, wherein:

2 said recessed step is off-centered with respect to a longitudinal axis of said slider body.

1       39. The negative pressure air bearing slider according to claim 31, further comprising:  
2       a first front air bearing platform; and  
3       a second front air bearing platform;  
4       said first and said second front air bearing platforms being disposed on opposite ends of  
5       said principal surface symmetrically about a longitudinal axis of said slider body, said first and  
6       second front air bearing platforms being disposed upstream of said U-shaped air bearing platform  
7       relative to said direction of flight of said slider.

1       40. The negative pressure air bearing slider according to claim 39, wherein:  
2       a tapered surface portion is interposed between said front edge and each of said first and  
3       said second front air bearing platforms, the tapered surface portion tapering from each air bearing  
4       surface toward said front edge of said slider body.

1       41. (Amended) The negative pressure air bearing slider according to claim 31, further  
2       comprising:  
3       a rear air bearing platform accommodating mounting of a transducer, said rear air bearing  
4       platform being spaced downstream of said U-shaped air bearing platform relative to said first  
5       direction, and being centered with respect to a longitudinal axis of said slider body.

1       42. (Amended) A negative pressure air bearing slider, comprising:  
2       a slider having a body with a principal surface disposed to confront a recording surface of

3 a recording medium, said principal surface having a lead portion and a rear portion, said lead  
4 portion being spaced upstream from said rear portion relative to a rotational direction of any  
5 recording medium confronted by said slider with a longitudinal axis of said slider extending  
6 between said lead portion and said rear portion defining a longitudinal direction of said slider and  
7 forming a tangent to said rotational direction, said lead portion having a front edge, said rear  
8 portion having a rear edge, said front edge and said rear edge together defining boundaries of said  
9 principal surface in said longitudinal direction of said slider; and

10 a U-shaped air bearing platform defining a negative pressure cavity on said principal  
11 surface, said U-shaped air bearing platform comprising not more than two separate air bearing  
12 platforms each extending from different and facing spaced-apart opposite ends of said not more  
13 than two separate air bearing platforms rearwardly toward said rear portion of said principal  
14 surface and respectively forming a first air bearing surface terminating said first side wall portion  
15 and forming a second air bearing surface terminating said second side wall portion, at least one  
16 of said not more than two separate air bearing platforms including a side wall portion with said  
17 U-shaped platform comprising an arcuately shaped front wall oriented toward said lead portion.

1 43. The negative pressure air bearing slider according to claim 42, further comprising a  
2 gap disposed within said cross rail portion.

1 44. The negative pressure air bearing slider according to claim 43, wherein said gap is  
2 centered with respect to said longitudinal axis of said slider body.

1        45. The negative pressure air bearing slider according to claim 43, wherein said gap is  
2        off-centered with respect to said longitudinal axis.

1        46. The negative pressure air bearing slider according to claim 42, further comprising a  
2        recessed step disposed within said cross rail portion.

1        47. The negative pressure air bearing slider according to claim 46, wherein said recessed  
2        step is centered with respect to said longitudinal axis.

1        48. The negative pressure air bearing slider according to claim 46, wherein said recessed  
2        step is off-centered with respect to said longitudinal axis.

1        49. The negative pressure air bearing slider according to claim 42, further comprising:  
2        a first front air bearing platform; and  
3        a second front air bearing platform;  
4        said first and said second front air bearing platforms being disposed on opposite sides of  
5        said principal surface symmetrically about said longitudinal axis of said slider body, said first  
6        and second front air bearing platforms being disposed upstream of said U-shaped air bearing  
7        platform relative to said rotational direction.

1        50. The negative pressure air bearing slider according to claim 49, further comprised of:

2        a tapered surface portion is interposed between said front edge and each of said first and  
3        said second front air bearing platforms, the tapered surface portion tapering from each air bearing  
4        surface toward said front edge of said slider body.

1        51. The negative pressure air bearing slider according to claim 42, further comprising a

2        rear air bearing platform accommodating mounting of a transducer, said rear air bearing platform  
3        being spaced downstream of said U-shaped air bearing platform relative to a rotational direction  
4        of said recording medium, and being centered with respect to said longitudinal axis of said slider  
5        body.

1        52. A negative pressure air bearing slider having a negative pressure cavity comprising:

2        a body with a principal surface disposed to confront a recording surface of a recording  
3        medium, said principal surface having a lead portion separated from a rear portion by a central  
4        portion, said lead portion and said central portion being spaced upstream from said rear portion  
5        relative to a rotational direction of any recording medium confronted by said slider, said lead  
6        portion having a front edge, said rear portion having a rear edge, said front edge and said rear  
7        edge together defining boundaries of longitudinal sides of said principal surface in a longitudinal  
8        direction of said slider body; and

9        a plurality of arcuately shaped arms each having distal ends extending from opposite ones  
10       of said longitudinal sides curving inwardly across said central portion of said principal surface

11 with spaced-apart proximal facing ends of said arms together forming a U-shaped air bearing  
12 platform located between said boundaries to separate a negative pressure cavity defined by said  
13 arms on said principal surface from said boundaries;

14 a distal end of at least one of said arms forming a terminal end wholly within said central  
15 portion and spaced-apart from said rear portion.

1 53. The negative pressure air bearing slider of claim 52, further comprising a cross-rail  
2 portion of said platform extending generally laterally across said principal surface and connecting  
3 said proximal facing ends.

1 54. The negative pressure air bearing slider of claim 52, further comprising said arms  
2 adjoining said boundaries.

1 55. A negative pressure air bearing slider having a negative pressure cavity comprising:  
2 a body with a principal surface disposed to confront a recording surface of a recording  
3 medium, said principal surface having a lead portion separated from a rear portion by a central  
4 portion, said lead portion and said central portion being spaced upstream from said rear portion  
5 relative to a rotational direction of any recording medium confronted by said slider, said lead  
6 portion having a front edge, said rear portion having a rear edge, said front edge and said rear  
7 edge together defining boundaries of longitudinal sides of said principal surface in a longitudinal  
8 direction of said slider body; and



9           a plurality of arcuately shaped arms each having distal ends extending from opposite ones  
10 of said longitudinal sides arcuately inwardly across said principal surface with spaced-apart  
11 proximal facing ends of said arms together forming a U-shaped air bearing platform located  
12 between said boundaries to separate a negative pressure cavity defined by said arms on said  
13 principal surface from said boundaries;

14           a distal end of at least one of said arms forming a terminal end wholly within said central  
15 portion and spaced-apart from said rear portion.

1           56. The negative pressure air bearing slider of claim 55, further comprising a cross-rail  
2 portion of said platform extending generally laterally across said principal surface and connecting  
3 said proximal facing ends.

1           57. The negative pressure air bearing slider of claim 55, further comprising said arms  
2 bordering said longitudinal sides.

1           58. A negative pressure air bearing slider having a negative pressure cavity comprising:  
2 a body with a principal surface disposed to confront a recording surface of a recording  
3 medium, said principal surface having a lead portion separated from a rear portion by a central  
4 portion, said lead portion and said central portion being spaced upstream from said rear portion  
5 relative to a rotational direction of any recording medium confronted by said slider, said lead  
6 portion having a front edge, said rear portion having a rear edge, said front edge and said rear

7 edge together defining boundaries of longitudinal edges of said principal surface in a longitudinal  
8 direction of said slider body, said central portion being formed by opposite longitudinal sides  
9 separated by a longitudinal center and bounded by said longitudinal edges; and

10 a plurality of arcuately shaped arms each having distal ends extending from opposite ones  
11 of said longitudinal sides curving inwardly across said central portion of said principal surface  
12 with spaced-apart proximal facing ends of said arms together forming a U-shaped air bearing  
13 platform located between said boundaries to separate a negative pressure cavity defined by said  
14 arms on said principal surface from said boundaries;

15 at least one of said distal ends forming a terminal end wholly within said central portion  
16 and spaced-apart from said rear portion.

1 59. The negative pressure air bearing slider of claim 58, further comprising a cross-rail  
2 portion of said platform extending generally laterally across said principal surface and connecting  
3 said proximal facing ends.

1 60. The negative pressure air bearing slider of claim 58, further comprising said arms  
2 adjoining said longitudinal edges.